



# Angular contact ball bearings

## 7317-B-TVP (Series 73..-B)

main dimensions to DIN 628-1, contact angle  $\alpha = 40^\circ$



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

(<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	85 mm
D	180 mm
B	41 mm
a	76 mm
D <sub>1</sub>	144 mm
d <sub>1</sub>	122 mm
D <sub>a</sub>	166 mm
max	
d <sub>a</sub>	99 mm
min	
D <sub>b</sub>	173 mm
max	
r <sub>1</sub>	1,1 mm
min	
r <sub>a1</sub>	1 mm
max	
r <sub>a</sub>	2,5 mm
max	
r <sub>min</sub>	3 mm
$\alpha$	40 ° Contact angle
m	4,26 kg Mass
C <sub>r</sub>	167000 N Basic dynamic load rating, radial
C <sub>0r</sub>	138000 N Basic static load rating, radial
n <sub>G</sub>	4450 1/min Limiting speed
n <sub>B</sub>	4100 1/min Reference speed
C <sub>ur</sub>	8100 N Fatigue limit load, radial

