



# Needle roller/axial cylindrical roller bearings ZARN2062-TV (Series ZARN)

## double direction

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	20 mm	
D	62 mm	
H	60 mm	
B	12,5 mm	
C	20 mm	
D <sub>1</sub>	52 mm	
D <sub>a</sub> max	53 mm	Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
d <sub>a</sub> min	38 mm	Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
H <sub>1</sub>	40 mm	
r <sub>1</sub> min	0,6 mm	
r <sub>min</sub>	0,3 mm	
m	0,87 kg	Mass
C <sub>a</sub>	64000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	141000 N	Basic static load rating, axial
C <sub>r</sub>	22600 N	Basic dynamic load rating, radial
C <sub>0r</sub>	36000 N	Basic static load rating, radial
n <sub>G</sub> 0i	6000 1/min	Limiting speed for oil lubrication (valid only with adequate oil cooling)
n <sub>G</sub>	1500 1/min	Limiting speed for grease lubrication

Fett	
MR <sub>L</sub>	1,3 Nm Bearing frictional torque
Ca <sub>L</sub>	2300 N/μm Axial rigidity
Ck <sub>L</sub>	400 Nm/mrad Tilting rigidity
M <sub>m</sub>	1,98 kg x cm <sup>2</sup> Mass moment of inertia for rotating inner ring
	1 μm Axial runout
	The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA20/52 Designation of recommended INA locknut
	AM20 Designation of recommended INA locknut
MA	38 Nm Tightening torque
	Only valid in conjunction with INA precision locknuts
	18448 N Axial preload force
	Locknuts not included in delivery.



