



## Plummer block housing units PASEY12 (Series PASEY)



cast iron housing, radial insert ball bearing with grub screws in inner ring, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d       12 mm         L       125 mm         H2       57 mm         A       30 mm         A1       18 mm         B       22 mm         H       30,2 mm         H1       10 mm         J       95 mm
H2       57 mm         A       30 mm         A1       18 mm         B       22 mm         H       30,2 mm         H1       10 mm
A 30 mm A1 18 mm B 22 mm H 30,2 mm H1 10 mm
A1 18 mm B 22 mm H 30,2 mm H1 10 mm
A1 18 mm B 22 mm H 30,2 mm H1 10 mm
B 22 mm H 30,2 mm H 10 mm
H 30,2 mm H1 10 mm
H <sub>1</sub> 10 mm
J 95 mm
N 11 mm
N <sub>1</sub> 19 mm
Q M6
S <sub>1</sub> 16 mm
m 0,44 kg Mass
Cr 10100 N Basic dynamic load rating, radial
Cor 4750 N Basic static load rating, radial
GG.ASE03 Designation of housing
GAY12-NPP-B Designation of bearing





