



# Angular contact ball bearings

## 7320-B-TVP (Series 73..-B)

main dimensions to DIN 628-1, contact angle  $\alpha = 40^\circ$



The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	100 mm
D	215 mm
B	47 mm
a	90 mm
D <sub>1</sub>	171,7 mm
d <sub>1</sub>	146,3 mm
D <sub>a</sub> max	201 mm
d <sub>a</sub> min	114 mm
D <sub>b</sub> max	208 mm
r <sub>1</sub> min	1,1 mm
r <sub>a1</sub> max	1 mm
r <sub>a</sub> max	2,5 mm
r <sub>min</sub>	3 mm
$\alpha$	40 ° Contact angle
m	7,16 kg Mass
C <sub>r</sub>	214000 N Basic dynamic load rating, radial
C <sub>0r</sub>	197000 N Basic static load rating, radial
n <sub>G</sub>	3700 1/min Limiting speed
n <sub>B</sub>	3550 1/min Reference speed
C <sub>ur</sub>	10600 N Fatigue limit load, radial

