

/medias/en!hp.ec.br.pr//medias/en!hp.pv/193.86.1.30NUP

2308-E-XL-TVP2NUP23..-EZylinderrollenlager

Cylindrical roller bearings

NUP2308-E-XL-TVP2 (Series NUP23..-E)

main dimensions to DIN 5412-1, locating bearing, separable, with cage

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system

(https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	40 mm
D	90 mm
B	33 mm
B ₃	5,5 mm
D ₁	75,9 mm
d ₁	57,6 mm
D _a max	81 mm
d _a min	49 mm
d _c min	60 mm
E	80 mm
F	52 mm
r ₁ min	1,5 mm
r _a max	1,5 mm
r _{min}	1,5 mm
m	0,999 kg Mass
C _r	132000 N Basic dynamic load rating, radial

C_{0r}	119000 N	Basic static load rating, radial
C_{ur}	21600 N	Fatigue limit load, radial
n_G	9500 1/min	Limiting speed
n_{ref}	5800 1/min	Reference speed



