



## Rod ends GAR20-UK (Series GAR..-UK)

with external thread, maintenance-free, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	20 mm	Tolerance: 0 / -0,01
d2	53 mm	
l2	104,5 mm	
	0 - 0,04 mm	Radial internal clearance
B	16 mm	Tolerance: 0 / -0,12
C <sub>1</sub>	13 mm	
D	35 mm	
d <sub>1</sub>	24,1 mm	
d <sub>3</sub>	M20X1,5	
dk	29 mm	
h	78 mm	
l <sub>1</sub>	43 mm	
l <sub>7</sub>	27 mm	
r <sub>1s</sub>	0,3 mm	Chamfer dimension
min		
α	9 °	
m	0,31 kg	Mass
C <sub>r</sub>	31300 N	Basic dynamic load rating, radial
C <sub>0r</sub>	75600 N	Basic static load rating, radial Basic load rating of housing

