



## Take-up housing units PHUSE35-XL (Series PHUSE)

cast iron and sheet steel housing, radial insert ball bearing with eccentric locking collar, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	35 mm
H	103 mm
A	28 mm
A2	22 mm
B1	39 mm
d <sub>3 max</sub>	55 mm
F	20 mm
G	65 mm
H1	52 mm
J	140 mm
J1	80 mm

K <sub>1</sub>	M12	
L	187 mm	
L <sub>1</sub>	50 mm	
N	11,5 mm	
Q	Rp1/8	
S	4 mm	
S <sub>1</sub>	29,5 mm	
V	98 mm	
m	2,46 kg	Mass
C <sub>0r G</sub>	15300 N	Load carrying capacity of housing, radial
C <sub>r</sub>	27500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	15300 N	Basic static load rating, radial
	HUE07 / HUSE07	Designation of housing
	GRAE35-XL-NPP-B	Designation of bearing

