



# Linear ball bearings KH14 (Series KH)

with preservative, not sealed, with relubrication facility

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

F <sub>w</sub>	14 mm
D	21 mm
L	28 mm
	Shaft diameter d <sub>Lw</sub> , Fase x
	d <sub>Lw</sub> ≤ 10: x = 1 tolerance +1
	10 < d <sub>Lw</sub> ≤ 30: x = 1,5 tolerance +1
	30 < d <sub>Lw</sub> ≤ 80: x = 2,5 tolerance +1
JL4	6 mm
N2	2,5 mm
	Supplied coated with a preservative
m	20,5 g Mass of bearing
	The basic load ratings are only valid for hardened (670+170 HV) and ground shaft raceways.
C <sub>min</sub>	690 N Basic dynamic load rating
C <sub>0</sub> min	520 N Basic static load rating
C <sub>max</sub>	830 N Basic dynamic load rating
C <sub>0</sub> max	760 N Basic static load rating
	Designs with anti-corrosion protection have the suffix -RR.

