



## Rod ends GAR10-UK (Series GAR..-UK)

with external thread, maintenance-free, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	10 mm	Tolerance: 0 / -0,008
d2	29 mm	
l2	62,5 mm	
	0 - 0,032 mm	Radial internal clearance
B	9 mm	Tolerance: 0 / -0,12
C <sub>1</sub>	7 mm	
D	19 mm	
d <sub>1</sub>	13,2 mm	
d <sub>3</sub>	M10	
dk	16 mm	
h	48 mm	
l <sub>1</sub>	26 mm	
l <sub>7</sub>	15 mm	
r <sub>1s</sub> min	0,3 mm	Chamfer dimension
α	12 °	
m	0,051 kg	Mass
C <sub>r</sub>	8640 N	Basic dynamic load rating, radial
C <sub>0r</sub>	20600 N	Basic static load rating, radial Basic load rating of housing

